


A

UTILITY PATENT APPLICATION TRANSMITTAL <small>(Only for new nonprovisional applications under 37 CFR 1.53(b))</small>	Attorney Docket No.	0557-4939-2X
	First Inventor or Application Identifier	Hiroshi TORIYA, et al.
	Title	GENERATION OF FREE-FORM SURFACE MODEL BY REVERSIBLE ROUNDING OPERATION
APPLICATION ELEMENTS <small>See MPEP chapter 600 concerning utility patent application contents</small>		ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231
<p>1. <input checked="" type="checkbox"/> Fee Transmittal Form (e.g. PTO/SB/17) (Submit an original and a duplicate for fee processing)</p> <p>2. <input checked="" type="checkbox"/> Specification Total Pages 37</p> <p>3. <input checked="" type="checkbox"/> Drawing(s) (35 U.S.C. 113) Total Sheets 14</p> <p>4. <input type="checkbox"/> Oath or Declaration Total Pages <input type="text"/></p> <p>a. <input type="checkbox"/> Newly executed (original or copy)</p> <p>b. <input type="checkbox"/> Copy from a prior application (37 C.F.R. §1.63(d)) (for continuation/divisional with box 15 completed)</p> <p>i. <input type="checkbox"/> DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §1.63(d)(2) and 1.33(b).</p> <p>5. <input type="checkbox"/> Incorporation By Reference (usable if box 4B is checked) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4B, is considered to be part of the disclosure of the accompanying application and is hereby incorporated by reference therein.</p>		ACCOMPANYING APPLICATION PARTS <p>6. <input type="checkbox"/> Assignment Papers (cover sheet & document(s))</p> <p>7. <input type="checkbox"/> 37 C.F.R. §3.73(b) Statement <input type="checkbox"/> Power of Attorney (when there is an assignee)</p> <p>8. <input type="checkbox"/> English Translation Document (if applicable)</p> <p>9. <input type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449 <input type="checkbox"/> Copies of IDS Citations</p> <p>10. <input type="checkbox"/> Preliminary Amendment</p> <p>11. <input checked="" type="checkbox"/> White Advance Serial No. Postcard</p> <p>12. <input type="checkbox"/> Small Entity Statement(s) <input type="checkbox"/> Statement filed in prior application. Status still proper and desired.</p> <p>13. <input type="checkbox"/> Certified Copy of Priority Document(s) (if foreign priority is claimed)</p> <p>14. <input checked="" type="checkbox"/> Other: Notice of Priority, List of Inventors' Names and Addresses</p>
<p>15. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below:</p> <p><input type="checkbox"/> Continuation <input type="checkbox"/> Divisional <input type="checkbox"/> Continuation-in-part (CIP) of prior application no.: Prior application information: Examiner: Group Art Unit:</p>		
<p>16. Amend the specification by inserting before the first line the sentence:</p> <p><input type="checkbox"/> This application is a <input type="checkbox"/> Continuation <input type="checkbox"/> Division <input type="checkbox"/> Continuation-in-part (CIP) of application Serial No. Filed on</p> <p><input type="checkbox"/> This application claims priority of provisional application Serial No. Filed</p>		
<p>17. CORRESPONDENCE ADDRESS</p> <p>OBLON, SPIVAK, MCCLELLAND, MAIER & NEUSTADT, P.C. FOURTH FLOOR 1755 JEFFERSON DAVIS HIGHWAY ARLINGTON, VIRGINIA 22202 (703) 413-3000 FACSIMILE: (703) 413-2220</p>		

Name:	Marvin J. Spivak	Registration No.:	24,913
Signature:		Date:	3/16/00
Name:	Registration Number 21,124	Registration No.:	

but PTO received check \$820.00
no check \$1,054.00
the PTO did not receive the following

+

Docket No. 0557-4939-2X

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

IN RE APPLICATION OF: Hiroshi TORIYA, et al.

FILING DATE: Herewith

FOR: GENERATION OF FREE-FORM SURFACE MODEL BY REVERSIBLE ROUNDING OPERATION

LIST OF INVENTORS' NAMES AND ADDRESSES

ASSISTANT COMMISSIONER FOR PATENTS
WASHINGTON, D.C. 20231

SIR:


Listed below are the names and addresses of the inventors for the above-identified patent application.

Hiroshi TORIYA	Tokyo, Japan
Tsuyoshi HARADA	Tokyo, Japan
Makoto YAJIMA	Tokyo, Japan
Rei WAKITA	Tokyo, Japan

A declaration containing all the necessary information will be submitted at a later date.

Respectfully Submitted,

OBLON, SPIVAK, McCLELLAND,
MAIER & NEUSTADT, P.C.



Marvin J. Spivak
Registration No. 24,913

C. Irvin McCl...
Registration Number 1,124

Fourth Floor
1755 Jefferson Davis Highway
Arlington, Virginia 22202
Tel. (703) 413-3000
Fax. (703) 413-2220
(OSMMN 11/98)

[illegible][illegible][illegible][illegible][illegible]

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention generally relates to a method of generating a free-form surface model based on
5 a reversible rounding operation, a method of generating a lattice polygon model from the generated free-form surface model, a record medium having a program embodied therein for practicing these methods, and a method of transmitting and displaying the free-form surface model.
10 The present invention particularly relates to a method generating a free-form surface model through a perfectly reversible rounding operation where an accurate free-form surface model can be generated.

2. Description of the Related Art

15 A shape represented by a lattice polygon model is characterized by its simple structure that is easy to design. A lattice polygon model can be turned into a free-form surface model by a rounding operation. Use of the rounding operation makes it possible to readily
20 generate a free-form surface model by designing a lattice polygon model. In the prior art, however, there is no known scheme to reconstruct an original lattice polygon model from a free-form surface model generated therefrom. Once a free-form surface model is generated,
25 the original lattice polygon model cannot be obtained

from the data of the generated model shape alone,
thereby preventing reuse of the lattice polygon model to
create another form.

In a network environment today, transfer and
5 exchange of 3D data are not performed on a frequent
basis. A standard representation of 3D shapes that is
used when transferring 3-dimensional data over a network
is VRML (Virtual Reality Modeling Language). In VRML,
data is represented by a set of flat planes that are
10 polygons. A polygon representation has a drawback in
that an increase in a level of detail of a represented
shape requires an increase in data size. In particular,
data that represents many free-form surfaces requires a
large number of polygons, resulting in an undesirably
15 large data size. This discourages transfer of data over
a network. A further problem is that when polygon-
representation data is transferred, a displayed shape
has a level of detail that can be decreased but cannot
be increased. In this manner, a 3D shape cannot be
20 represented with sufficient quality if a small data size
is used, thereby severely discouraging use of 3D data in
a network environment.

In another field of endeavor, 3D-CAD systems
used in manufacturing industries use a data-
25 representation scheme that represents a solid model

having detailed free-form surface data. Such data representation is now beginning to be supported by standard formats such as IGES (Initial Graphic Exchange Specification) or STEP (Standard for the Exchange of Product Model Data). In the world of CAD, a precise shape-representation scheme called a trimmed free-form surface has been used for the purpose of representing generated free-form surfaces with high accuracy. Such schemes are suitable for highly accurate representation of shape. Because of a required large data size, however, it is difficult to use these schemes in the network environment.

Reversible rounding schemes known to date include those disclosed in: (1) Japanese Patent Laid-open Application No. 9-314697; (2) Atsushi Nakamura, "A Study on Free-form Deformation with Rounding Operation," a Master's Thesis with Keio University, Graduate School of Media and Governance, 1998; and (3) Yuichiro Chaki, "A Study on Flexible Surface Control by Control Lattice," a Master's Thesis with Keio University, Graduate School of Media and Governance, 1998. These schemes are not perfect, however, in that there is a requirement, among others, that all surfaces constituting polygons be coplanar.

There is another scheme called a subdivision

surface. This scheme generates a pseudo free-form surface model by subdividing a polygon model. This scheme maintains reversibility, but is only a scheme for generating subdivided polygon models for the purpose of display. This scheme is inherently different from a scheme that generates a precise free-form surface model.

The VRML, which is a representation scheme used in the network environment, is based on use of polygons. As previously noted, a polygon-based representation has a drawback in that as an increased level of detail is pursued, data size inevitably increases. If attempt is made to represent a complex shape with a small amount of data, quality of shape representation is degraded, resulting in a lower display quality.

SUMMARY OF THE INVENTION

It is a general object of the present invention to provide a rounding operation that substantially obviates one or more of the problems caused by the limitations and disadvantages of the related art.

It is another and more specific object of the present invention to provide a rounding operation that generates a free-form surface model having the same

topological structure (i.e., the same connections
between shape elements) as a lattice polygon model, and
matches pairs of vertices between the two models by
linear transformation, thereby providing for the
5 reconstruction of the original lattice polygon model
from the generated free-form surface model.

In one aspect, the present invention generates
a free-form surface model having an identical
topological structure to the original lattice polygon
10 model, and matches vertices of the lattice polygon model
with vertices of the free-form surface model such as to
allow coordinates of a matched vertex to be obtained
through linear transformation, followed by generating
unique control points of curves of the free-form surface
15 model from the vertices of the free-form surface model,
thereby attaining a reversible rounding operation.

In another aspect, the present invention
provides rounding information for each lattice polygon
model, so that data of a lattice structure can be
20 generated from an externally provided free-form surface
model. Further, the present invention represents all
the shapes by interpolated free-form surface data, and
represents free-form surface structures by abstract
lattice structures, thereby making it possible to
25 represent a 3D shape by a relatively small amount of

data. Moreover, the present invention stores data of
lattice structures in a server, and provides a client
with a viewer that interprets a lattice structure and
displays the lattice structure as free-form surface data
5 or as detailed polygon-model data that generates a
polygon model from free-form surface data, thereby
achieving high-speed 3D-data transfer and display
thereof.

Other features and advantages of the present
10 invention will be set forth in the description which
follows, and in part will become apparent from the
description and the accompanying drawings, or may be
learned by practice of the invention according to the
teachings provided in the description. Objects as well
15 as the features and advantages of the present invention
will be realized and attained by a rounding operation
particularly pointed out in the specification in such
full, clear, concise, and exact terms as to enable a
person having ordinary skill in the art to practice the
20 invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig.1 is an illustrative drawing showing a
lattice polygon model;

25 Fig.2 is an illustrative drawing for

explaining generation of center points of surfaces and midpoints of edges with respect to the lattice polygon model of Fig.1;

Fig.3 is an illustrative drawing showing a
5 quadrilateral division of the lattice polygon model;

Fig.4 is an illustrative drawing for explaining how to obtain center points for generated quadrilaterals;

Fig.5 is an illustrative drawing for
10 explaining how to obtain vertices of a free-form surface model;

Fig.6 is an illustrative drawing for explaining how to obtain tangents to an edge of the free-form surface model;

Fig.7 is an illustrative drawing for
15 explaining how to determine the free-form surface model;

Fig.8 is an illustrative drawing for explaining how to determine control points;

Figs.9A and 9B are illustrative drawings
20 respectively showing a lattice polygon model and a free-form surface model generated according to the present invention;

Fig.10 is a block diagram showing a configuration of a first embodiment according to the
25 present invention;

Fig.11 is a flowchart of a process according to the first embodiment of the present invention;

Fig.12 is a block diagram showing a computer-based implementation of the present invention;

5 Figs.13A through 13D are tables showing data structures used in the present invention;

Fig.14 is an illustrative drawing providing a brief overlook of a second embodiment of the present invention;

10 Fig.15 is an illustrative drawing showing a configuration of a system according to the second embodiment of the present invention.

Fig.16 is an illustrative drawing showing a data structure of shape information included in an XVL file according to the second embodiment of the present invention;

Fig.17 is an illustrative drawing for explaining a rounding coefficient;

20 Figs.18A and 18B are illustrative drawings showing a human model represented in an XVL format and an example of shading display thereof; and

Fig.19 is a drawing showing an example of real model generation.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

In the following, embodiments of the present invention will be described with reference to the accompanying drawings.

5 Figs.13A through 13D are tables showing data structures used in a first embodiment of the present invention.

 A vertex-coordinate table 200 of Fig.13A stores therein 3-dimensional coordinates (x, y, z) of
10 each vertex of a polygon model, which is also referred to as a lattice polygon model. The vertex-coordinate table 200 also stores therein 3-dimensional coordinates of vertices of a free-form surface model that is
15 later. The vertices of the lattice polygon model and the vertices of the free-form surface model are paired in the table.

 A surface-index table 300 of Fig.13B represents vertices of each polygon of a lattice polygon
20 model by a series of index values, each of which indicates a row number of a row in the vertex-coordinate table 200. The size of the surface-index table 300 is equal to the number of lattice polygons.

 An edge-index table 400 of Fig.13C represents
25 edges of a lattice polygon model and a free-form surface

model where the edges are each represented by a pair of vertices (i.e., a start point and an end point). The start points and the end points are indices to the rows of vertex-coordinate table 200. In the case of a free-form surface model, pairs of control points that are obtained when transforming a straight-line edge into a cubic Bezier curve are added in the edge-index table 400. These control points are indices to a control-point-coordinate table 500, which is shown in Fig.13D.

10 Fig.10 is a functional block diagram showing a configuration of a first embodiment of the present invention.

A vertex-calculation unit 10 calculates vertices of a free-form surface model that correspond to vertices of a lattice polygon model referred to in the vertex-coordinate table 200 by the surface-index table 300. Coordinates of these new vertices are calculated from linear transformation of coordinates of original vertices. The coordinates of the vertices of the free-form surface model are stored in their designated places in the vertex-coordinate table 200.

An edge-determination unit 20 refers to the vertex-coordinate table 200, the surface-index table 300, and the edge-index table 400, and determines edge geometries of the free-form surface model that

correspond to edges of the lattice polygon model. The edge geometries of the free-form surface model are represented by cubic Bezier curves, so that control points are generated to represent the curves, and are
5 stored in the control-point-coordinate table 500. Further, indices to the entries of the control-point-coordinate table 500 are stored in their designated places in the edge-index table 400.

A free-form-surface-generation unit 30 refers
10 to the vertex-coordinate table 200, the surface-index table 300, and the edge-index table 400, and interpolates Gregory free-form surfaces into the free-form surface model comprised of cubic Bezier curves. This results in a free-form surface model having the
15 same topological structure as the lattice polygon model.

The coordinates of vertices of the free-form surface model, which are obtained by transforming the lattice polygon model, are obtained as a linear transformation of the coordinates of vertices of the
20 lattice polygon model. Namely, with vertices of the lattice polygon model being V_i , new vertices P_j are represented by an equation (1) as follows:

$$P_j = \sum_{i=1}^n K_{ij} V_i \quad (j=1, 2, \dots, n) \quad (1)$$

where n is the number of vertices. A linear

transformation has an inverse transformation thereof.
Namely, the vertices V_i can be obtained by an equation
(2) as follows.

$$V_i = \sum_{j=1}^n l_{ij} P_j \quad (i=1, 2, \dots, n) \quad (2)$$

5 In this manner, vertex coordinates of the
original lattice polygon model can be derived from
vertex coordinates of the obtained free-form surface
model. By placing straight-line edges between the
derived vertices, the original lattice polygon model can
10 be reconstructed. Namely, an inverse rounding operation
is attained. Further, data of the lattice polygon model
may be transferred via a network, and the rounding
operation is applied to the data at a client PC of the
receiver end to generate a free-form surface model.
15 Further, the data may be displayed as a detailed polygon
model.

Fig.11 is a flowchart of a process according
to this embodiment. The process will be described with
reference to a lattice polygon model shown in Fig.1

20

STEP1

(I) All the surfaces A constituting the
lattice polygon model in Fig.1 are divided into
quadrilaterals. To this end, center points C of the

surfaces A and midpoints D of the edges B are obtained as shown in Fig.2. A center of a surface is derived by obtaining averages of coordinates of the vertices V_i that make up the surface. When deriving the surface center, weights may be given to the vertices so as to change a position of the surface center C and the midpoints D. As shown in Fig.3, the quadrilateral division of the surfaces A is carried out by drawing lines between the surface center C and the midpoints D of the edges B.

(II) A center F of a given quadrilateral E generated as described above is obtained from the vertices of the given quadrilateral E as shown in Fig.4. As in the case described above, the center F is calculated by obtaining averages of coordinates of the vertices that constitute the quadrilateral where weights may be given to the vertices.

(III) As shown in Fig.5, a polygon H is generated by connecting the centers F of the quadrilaterals around a vertex G of the original lattice polygon model. Then, a center P0 of the vertices of the polygon H is obtained. P0 becomes a vertex of a new surface model corresponding to the vertex G. As in the case described above, the center P0 is calculated by obtaining averages of coordinates of the vertices that

constitute the polygon where weights may be given to the vertices. The center P_0 is a vertex of the free-form surface model that corresponds to the vertex G of the original lattice polygon model. As described

5 hereinbefore, in terms of coordinates, the center P_0 is an average of the center points F , each of which is an average of the center point C and the midpoints D where the center point C and the midpoints D are averages of the vertices of the lattice polygon model. Therefore,
10 the center point P_0 is represented as a linear transformation of vertices of the original lattice polygon model.

STEP2

15 (I) As shown in Fig.6, the center point P_0 and a midpoint Q of an edge I of the polygon H are connected to define a vector P_0Q .

 (II) A shape of a curve is defined such that the vector as defined above is a tangent to the curve.

20 For example, a shape of a curve corresponding to a straight line B as shown in Fig.7 will be obtained. End points of the curve are the point P_0 and the point P_3 . As shown in Fig.8, a vector P_3R is defined in the same manner as for the vector P_0Q by connecting between the
25 center point (new vertex) P_3 and a midpoint R of a

5

$$P_3P_2 = (4/3)P_3R$$

10

15

20

25

Fig.9A is an illustrative drawing showing a lattice polygon model. Fig.9B is an illustrative drawing showing a free-form surface model generated according to the present invention. The lattice polygon model of Fig.9A and the free-form surface model of

Fig.9B have one-to-one correspondences therebetween in terms of vertices, edges, and surfaces. The inverse rounding operation thus can be applied to the shape shown in Fig.9B to generate the shape shown in Fig.9A.

5 The present invention is not limited to the embodiment described above, but can be applicable by use of a computer system as shown in Fig.12.

 An input unit 1 is comprised of a keyboard, a mouse, a touch panel, etc., and is used for entering
10 information. An output unit 2 outputs various output information and information entered by using the input unit 1, and is comprised of a display device, a printer, or the like. A CPU 3 executes various programs. A memory 4 stores therein the programs, and, also, serves
15 as a temporal storage to store information generated during execution of the programs. A memory unit 5 stores therein the programs, data, information generated during program execution, etc. A memory-media driving unit 6 has a memory medium mounted therein for recording
20 programs and data, and reads the programs and data from the memory medium to supply them to the memory 4 and/or the memory unit 5. The memory-media driving unit 6 may also be used as a temporal storage for data input/output and/or for providing memory space for execution of the
25 programs.

In such a computer configuration, each function shown in Fig.10 is implemented as a program or a program unit, and is recorded in a memory medium such as a CD-ROM. The CD-ROM is then mounted in a CD-ROM
5 drive of a computer, and each program is loaded into the computer to carry out a corresponding function of the present invention.

The memory medium may be a semiconductor medium such as a ROM, an IC memory card, etc., an
10 optical medium such as a DVD-ROM, an MO, an MD, a CD-R, etc., or a magnetic medium such as a magnetic tape, a flexible disc, etc.

Further, the programs for implementing the functions of the present invention may be provided via a
15 communication medium rather than via a memory medium.

In the following, a second embodiment of the present invention will be described.

Fig.14 is an illustrative drawing providing a brief overview of the second embodiment of the present
20 invention.

In this second embodiment, a lattice structure that is a combination of a lattice polygon model and rounding information is used for representing shape rather than using a polygon structure that roughly
25 approximates an original shape. Use of such a lattice

structure enables free-form surfaces to be represented with high accuracy. Further, such a lattice structure can be transferred over a network because of a small data size thereof. In the first embodiment, a rounding operation generates a free-form surface model from a lattice polygon model alone. In the second embodiment, on the other hand, rounding information about lattice points and edges is provided in addition to the lattice polygon model, so that the rounding operation is applied to the combination of the model and the information, which may be transferred via a network to enable a client PC to process the data. A lattice kernel provided in the PC, which receives a lattice structure via high-speed data transfer, analyzes the lattice structure and generates free-form surface data from the lattice structure. The lattice kernel then displays the free-form surface data by using a detailed polygon model, thereby reconstructing with a high-speed CPU an image that looks real. Hereinafter, this new format is called XVL (extended VRML with lattice). When used on the Internet, the XVL data is attached to an HTML or XML file in the same manner as is VRML data.

Use of XVL achieves such representation and transfer of 3D data as follows.

(1) Shape is represented by a lattice

structure that is a combination of a lattice polygon
model and rounding information, so that a 3D shape can
be represented by a relatively small amount of data
compared with detailed-polygon data or free-form surface
5 data.

(2) 3D modeling software is provided with a
function (i.e., rounding function) to transform a
lattice structure into a surface structure (i.e., free-
form surface model), so that a shape having a surface
10 structure can be readily designed.

(3) A function (i.e., inverse rounding
function) to transform a surface structure into a
lattice structure is provided, thereby making it
possible to transform existing free-form surface data
15 easily into data in the XVL format.

(4) A viewer has the rounding function built
therein to transform a lattice structure into a surface
structure, so that the viewer can analyze an XVL file
having a relatively small file size that is easy to
20 transfer at a high transfer rate, thereby providing a
basis for high-quality 3D display.

Fig.15 is an illustrative drawing showing a
configuration of a system according to the second
embodiment of the present invention.

25 When the XVL format of the present invention

is used for processing shape data, the XVL format requires around one tenth to one twentieth of the data size required in the VRML format. In the case of the second embodiment, the data size may be $4/3$ times as much as the data size of the first embodiment. Such a small amount of data makes it possible to achieve a high-speed transfer of 3D data that looks real when displayed.

A server 41 includes an XVL input device 51 and an XVL conversion device 52. The XVL input device 51 is used when data in the XVL format is entered. The XVL conversion device 52 generates an XVL file by applying an inverse rounding operation of the present invention to existing free-form surface data. The server 41 delivers XVL files via a network 42. A client PC 43 and a client PC 44 each include an XVL expansion device 53. The client PC 44 is configured to include the XVL input device 51 and the XVL conversion device 52, so that the client PC 44 can attend to conversion of existing free-form surface data or generation of XVL-format data. Each device may be implemented as software.

[Representation of XVL]

Fig.16 is an illustrative drawing showing a data structure of shape information included in an XVL

file according to the second embodiment of the present invention.

A lattice polygon model has the same data structure as that described in connection with the first
5 embodiment. A method of describing a lattice structure (i.e., a lattice polygon model plus rounding information) in a file will be explained below.

A lattice polygon model is represented as normal polygon data (which is referred to herein as
10 lattice polygon data). Namely, the lattice polygon model is represented by an array including coordinates of vertices that constitute lattice polygons and by an index array that specifies connections between the vertices to represent the lattice polygons. In the XVL
15 format, rounding information attached to each vertex and each edge is provided in addition to the lattice information, thereby permitting fine control of free-form surface shapes. The rounding information includes an index specifying a vertex and a rounding coefficient
20 of the indicated vertex with respect to each of the vertices. The rounding information further includes an index specifying an edge (i.e., a pair of indices indicating two end points of the edge), a rounding coefficient of the edge, a start-point rounding vector
25 (i.e., vector that defines a tangent vector on the side

of the start point of the edge), and an end-point
rounding vector (i.e., vector that defines a tangent
vector on the side of the end point of the edge) with
respect to each of the edges. Here, the indices each
5 indicate numbers indicative of array elements in the
array that includes coordinates of vertices constituting
the lattice polygon data.

A rounding coefficient of an indicated vertex
or an indicated edge specifies how close a corresponding
10 portion of a generated free-form surface shape comes to
the indicated vertex or to the indicated edge. As the
rounding coefficient approaches zero, the free-form
surface shape has the corresponding portion thereof
closer to the lattice vertex or edge. As the rounding
15 coefficient becomes larger, the free-form surface shape
becomes rounder. The start-point rounding vector and
the end-point rounding vector are used when a lattice
structure is reconstructed by applying an inverse
rounding operation to a free-form surface model. These
20 vectors relate to information about roundness of a cubic
Bezier curve, and define tangent vectors at the start
point and the end point of the curve. If a given shape
model can be converted into a free-form surface model
comprised of edges that are all represented by either a
25 cubic Bezier curve or a straight line, such a shape can

be described in the XVL format. In such a case, the start-point vector and the end-point vector are added to the edge rounding information.

In the following, a process of the second
5 embodiment will be described with reference to the lattice polygon model shown in Fig.1. This description is provided to supplement the description provided in connection with the first embodiment.

At STEP1 (II) in the first embodiment, a
10 center point (i.e., a coordinate average) of vertices that constitute a generated quadrilateral is obtained so as to create a new vertex inside the quadrilateral (Fig.4).

The rounding coefficient changes the way the
15 new vertex is obtained. When the rounding coefficient is specified, a new vertex inside a quadrilateral is obtained, as shown in Fig.17, after changing u and v from their standard values 0.5 on the u-v parameter space of the quadrilateral.

20 When the rounding coefficient of the vertex G is set to 0.2 (smaller than its standard value), parameters u and v of each relevant quadrilateral are each set to 0.2. As a result, a vertex of a free-form surface model generated at the step STEP1 comes closer
25 to the vertex G, so that the generated free-form surface

model has a shape closer to the original lattice polygon model. If the rounding coefficient of a vertex is set to a value larger than the standard value, a rounded free-form surface model is generated, having a

5 corresponding vertex farther away from the vertex of the original lattice polygon model compared to when the standard value is used.

If the rounding coefficient of the edge B (i.e., the rounding coefficient of the midpoint D of the
10 edge B) is set to a value smaller than its standard value, parameters u' and v' of quadrilaterals relating to the edge B are set to a smaller value. As a result, an edge of a free-form surface model generated at the step STEP1 comes closer to the edge B of the lattice
15 polygon model, so that the generated free-form surface model has a shape closer to the original lattice polygon model. If the rounding coefficient of an edge is set to a value larger than the standard value, a rounded free-form surface model is generated, having a
20 corresponding edge farther away from the edge of the original lattice polygon model compared to when the standard value is used.

[Example]

25 According to the second embodiment of the

present invention, a surface model generated from an original lattice structure that is a lattice polygon model of Fig.9A plus some rounding information may be a shape that adds some roundness or sharpness to the vertices and/or edges shown in Fig.9B. The surface model corresponding to the shape of Fig.9B may undergo the inverse rounding operation, thereby generating the shape of Fig.9A. As the shape of Fig.9A is represented in the XVL format, data size of the output data can be reduced by a significant amount.

Figs.18A and 18B are illustrative drawings showing a human model represented in the XVL format and an example of shading display thereof. The XVL data shown in Fig.18A has a relatively small data size (44 Kbytes in this example), it can be easily transmitted via a network. Based on this lattice polygon model, a surface model is created as shown in Fig.18B. When this function is implemented in a viewer, such a configuration makes it possible to read XVL over a network and attend to 3-dimensional display that looks real in the network environment. Further, when a surface model generated from an XVL format is supplied in a data format that can be used in a RP (Rapid Prototyping) device, a real model as shown in Fig.19 can be created. Further, if data for use in a CAM system is

generated from the surface model, the real model as described above can be further processed for manipulation and changing of shape.

As is apparent from the description provided above, the present invention generates a free-form surface model that has one-to-one correspondences with the original polygon model in terms of vertices, edges, and surfaces, thereby providing a perfectly reversible rounding operation. Since the polygon model and the free-form surface model have the same topology, the free-form surface model can inherit attributes given to the original polygon model. Namely, attributes such as colors and textures provided for the lattice polygon model can be passed on to the free-form surface model. This is one of the advantages that is difficult to attain in the related art.

According to the XVL format of the present invention, data has a lattice structure that includes a surface structure. The XVL format thus has an advantage in that a relatively small data size suffices to represent shape while high quality of data representation is maintained.

According to the XVL format of the present invention, free-form surface shape is represented by interpolating free-form surfaces that are defined by a

lattice structure, which is a combination of lattice
information and rounding information. This approach
achieves a certain level of accuracy while reducing a
data size. Because of a small data size, use of data in
5 a network environment is viable. Further, data
representation of free-form surfaces provides for
application of XVL data in CAD/CAM systems.

Further, the present invention is not limited
to these embodiments, but various variations and
10 modifications may be made without departing from the
scope of the present invention.

The present application is in part based on
Japanese priority application No. 12-001136 filed on
January 6, 2000 with the Japanese Patent Office, the
15 entire contents of which are hereby incorporated by
reference.

WHAT IS CLAIMED IS

5

1. A method of generating a free-form surface model, comprising the steps of:

applying linear transformation to a lattice polygon model to generate vertices of a free-form surface model corresponding to respective vertices of the lattice polygon model; and
generating control points of cubic Bezier curves that connect the vertices of the free-form surface model, and that correspond to respective edges of the lattice polygon model.

20

2. The method as claimed in claim 1, further comprising a step of interpolating Gregory patches into a mesh comprised of the cubic Bezier curves.

25

3. The method as claimed in claim 1, further comprising a step of adding rounding information to the lattice polygon model, the rounding information controlling how round the free-form surface model is
5 when the free-form surface model is generated from the lattice polygon model and the rounding information, wherein said step of applying linear transformation includes a step of generating the vertices of the free-form surface model by utilizing the rounding information.

10

4. The method as claimed in claim 3, wherein
15 said rounding information includes rounding information attached to the vertices and the edges of the lattice polygon model.

20

5. The method as claimed in claim 1, further comprising a step of reconstructing the lattice polygon model from the free-form surface model by utilizing an
25 inverse transformation of the linear transformation.

6. A computer-readable memory medium having a program embodied therein for causing a computer to generate a free-form surface model, said program comprising program code units configured to perform the
5 steps of:

applying linear transformation to a lattice polygon model to generate vertices of a free-form surface model corresponding to respective vertices of the lattice polygon model; and

10 generating control points of cubic Bezier curves that connect the vertices of the free-form surface model, and that correspond to respective edges of the lattice polygon model.

15

7. The computer-readable memory medium as claimed in claim 6, further comprising a step of
20 interpolating Gregory patches into a mesh comprised of the cubic Bezier curves.

25

8. The computer-readable memory medium as claimed in claim 6, further comprising a step of adding rounding information to the lattice polygon model, the rounding information controlling how round the free-form
5 surface model is when the free-form surface model is generated from the lattice polygon model and the rounding information, wherein said step of applying linear transformation includes a step of generating the vertices of the free-form surface model by utilizing the
10 rounding information.

9. The computer-readable memory medium as claimed in claim 8, wherein said rounding information includes rounding information attached to the vertices and the edges of the lattice polygon model.

20

10. The computer-readable memory medium as claimed in claim 6, further comprising a step of
25 reconstructing the lattice polygon model from the free-

form surface model by utilizing an inverse transformation of the linear transformation.

5

11. A method of transmitting 3D data via a network, comprising the steps of:

adding rounding information to a lattice
10 polygon model, the rounding information controlling how
round a free-form surface model is when the free-form
surface model is generated from the lattice polygon
model and the rounding information by applying linear
transformation to the lattice polygon model to generate
15 vertices of the free-form surface model corresponding to
respective vertices of the lattice polygon model, and
generating control points of cubic Bezier curves that
connect the vertices of the free-form surface model, and
that correspond to respective edges of the lattice
20 polygon model; and

transmitting the lattice polygon model and the
rounding information over the network.

25

12. A method of generating a free-form surface model, comprising the steps of:

receiving a lattice polygon model and rounding
5 information via a network;

applying linear transformation to the lattice polygon model to generate vertices of a free-form surface model corresponding to respective vertices of the lattice polygon model; and

10 generating control points of cubic Bezier curves that serve as edges to connect the vertices of the free-form surface model, and that correspond to respective edges of the lattice polygon model, wherein the rounding information controls how close the vertices
15 and edges of the free-form surface model are to the respective vertices and edges of the lattice polygon model.

20

13. A server device for transmitting 3D data via a network, configured to add rounding information to a lattice polygon model, the rounding information
25 controlling how round a free-form surface model is when

the free-form surface model is generated from the
lattice polygon model and the rounding information by
applying linear transformation to the lattice polygon
model to generate vertices of the free-form surface
5 model corresponding to respective vertices of the
lattice polygon model, and generating control points of
cubic Bezier curves that connect the vertices of the
free-form surface model, and that correspond to
respective edges of the lattice polygon model; and to
10 transmit the lattice polygon model and the rounding
information over the network.

15

14. A client device connected to a network,
configured to receive a lattice polygon model and
rounding information via the network; to apply linear
transformation to the lattice polygon model to generate
20 vertices of a free-form surface model corresponding to
respective vertices of the lattice polygon model; and to
generate control points of cubic Bezier curves that
serve as edges to connect the vertices of the free-form
surface model, and that correspond to respective edges
25 of the lattice polygon model, wherein the rounding

information controls how close the vertices and edges of the free-form surface model are to the respective vertices and edges of the lattice polygon model.

ABSTRACT OF THE DISCLOSURE

A method of generating a free-form surface model includes the steps of applying linear transformation to a lattice polygon model to generate vertices of a free-form surface model corresponding to respective vertices of the lattice polygon model, and generating control points of cubic Bezier curves that connect the vertices of the free-form surface model, and that correspond to respective edges of the lattice polygon model.

FIG.1




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6




FIG.7





FIG.8






FIG. 9A




FIG. 9B

009180-86592560

FIG.10




FIG.11




FIG.12




FIG.13A

INDEX ↓	COORDINATES (x,y,z) LATTICE POLYGON MODEL	COORDINATES (x,y,z) OF FREE-FORM-SURFACE MODEL
P0		
P1		
P2		
:		
Pn		

FIG.13B

EACH ROW INCLUDING INDICES OF VERTEX-COORDINATE TABLE	P0	P1	P2		
	P2	P1	P7	P5	
	P5	P7	P3	P8	P4

FIG.13C

EACH ROW INCLUDING INDICES OF VERTEX-COORDINATE TABLE	START POINT	END POINT	CONTROL POINT 1	CONTROL POINT 2
	P0	P1	C0	C1
	P1	P2	C2	C3
	P2	P3	C4	C5

FIG.13D

INDEX ↓	COORDINATES (x,y,z)
C0	
C1	
C2	
:	
Ck	

FIG.14




FIG.15




FIG.16





FIG.17






FIG. 18B




FIG. 18A

009160-85542600




FIG.19

003120-333360